# **MY24 MAVERICK DS TURBO RR**



#### **HIGHLIGHTS**

- Smart-Lok<sup>™</sup> front differential
- SHOWA HPG piggyback 2.5 shocks
- High torque Dynamic Power Steering (DPS)
- Belt monitoring system
- 850 W Magneto
- 14 in. (35.6 cm) cast-aluminum wheels
- 30 in. (76.2 cm) Maxxis Carnivore† tires
- 4.5 in. (11.4 cm) digital display with keypad
- · Pear tow hool
- · Horn & Buzzer

#### **ENGINE**

| Туре                 | 149 kW (200 hp*), Rotax® ACE (Advanced Combustion<br>Efficiency) 900 cc Turbocharged Triple-cylinder engine,<br>liquid cooled with integrated intercooler and high-<br>performance air filter |
|----------------------|---|
| Fuel Delivery System | Intelligent Throttle Control (iTC™) with Electronic Fuel Injection (EFI)  |
| Transmission         | PDrive primary and Quick Response System X (QRS-X) CVT with high airflow, L / H / N / R / P   |
| Drive Train          | Lockable front differential with exclusive Smart-Lok<br>technology. True 2WD/4WD with front diff. lock / 4WD<br>TRAIL ACTIV/ 4WD TRAIL  |
| Power Steering       | High torque Tri-Mode Dynamic Power Steering (DPS™)  |
|                      |   |

#### SUSPENSIONS

| Front Suspension | Double A-arm with sway bar / 20 in. (50.8 cm) travel                          |
|------------------|---|
| Front Shocks     | SHOWA HPG piggyback 2.5<br>(Dual Speed Compression, Dual-rate spring)         |
| Rear Suspension  | 4-link Torsional Trailing-arm X (TTX) with sway bar / 20 in. (50.8 cm) travel |
| Rear Shocks      | SHOWA HPG piggyback 2.5<br>(Dual Speed Compression, Dual-rate spring)         |
|                  |   |

## TIRES / WHEELS

| Front & Rear Tires | Maxxis Carnivore† 30 x 10 / 10 x 14 in. (76.2 x 25.4 / 25.4 x 35.6 cm) |
|--------------------|--|
| Wheels             | 14 in. (35.6 cm) cast-aluminum   |

## BRAKES

| Front | Dual 262 mm disc brakes with hydraulic twin-piston calipers |
|-------|---|
| Rear  | Dual 248 mm disc brakes with hydraulic twin-piston calipers |

## **DIMENSIONS / CAPACITIES**

| Estimated Dry Weight ** | 1,546 lb (701.3 kg)                            |
|-------------------------|--|
| Chassis / Cage          | Dual-phase 980 steel                           |
| LxWxH                   | 132 x 64 x 65.4 in. (335.3 x 162.5 x 166.1 cm) |
| Wheelbase               | 102 in. (259.1 cm)                             |
| Ground Clearance        | 14 in. (35.6 cm)                               |
| Rack Capacity           | 200 lb (91 kg) with LinQ™ quick-attach         |
| Storage Capacity        | Total: 2.5 gal (9.4 L)                         |
| Fuel Capacity           | 10.5 gal (40 L)                                |
|                         |  |

## **FEATURES**

| Gauge           | 4.5 in. (11.4 cm) wide digital display with keypad                                 |
|-----------------|--|
| Instrumentation | DC Outlet (10-A)   |
| Magneto         | 850 W  |
| Ingnition       | RF Digitally Encoded Security System (D.E.S.S.™) with Start / Stop button          |
| Lighting        | LED headlights<br>LED tail lights  |
| Winch           | N/A  |
| Protection      | Integrated front bumper<br>Quarter-doors<br>HMWPE full skid plate<br>Rear tow hook |

### WARRANTY

| *************************************** |                             |
|---|-----------------------------|
| Factory warranty                        | 2-year BRP limited warranty |
|   |                             |

<sup>\*149</sup>kw/200hp based on MY22 U.S. EPA certification, or 145kw/195hp based on current EU NRMM certification.





