MY24 MAVERICK MAX X RS TURBO RR



Fuel Injection (EFI)

ACTIV / 4WD TRAIL

/ Trophy truck inspired arms

22 in. (55.9 cm) travel

adjustments

piston calipers

piston calipers

149 kW (200 hp*), Rotax® ACE (Advanced Combustion Efficiency) 900 cc Turbocharged Triple-cylinder engine, liquid cooled with integrated intercooler and high-performance air filter Intelligent Throttle Control (iTC™) with Electronic

PDrive primary and Quick Response System X (QRS-X) CVT with high airflow, L / H / N / R / P

High torque Tri-Mode Dynamic Power Steering

Lockable front differential with exclusive Smart-Lok.
True 2WD/4WD with front diff. lock / 4WD TRAIL

Double A-arm with sway bar / 22 in. (55.9 cm) travel

4-link Torsional Trailing-arm X (TTX) with sway bar /

FOX† 2.5 PODIUM RC2† Piggyback with bypass, dual speed compression and rebound adjustments

FOX† 3.0 PODIUM RC2† remote reservoir with bypass, dual speed compression and rebound

Maxxis Carnivore† 32 x 10 / 10 x 14 in. (81.3 x 25.4 / 25.4 x 35.6 cm)

14 in. (35.6 cm) cast-aluminum beadlock

Dual 262 mm disc brakes with hydraulic twin-

Dual 248 mm disc brakes with hydraulic twin-

Fiery Red - Hyper Silver

ENGINE

Fuel Delivery System

Transmission

Power Steering

SUSPENSIONS

Front Shocks

Rear Shocks

Wheels

BRAKES

Front

Rear

Front Suspension

Rear Suspension

TIRES / WHEELS
Front & Rear Tires

Drive Train

HIGHLIGHTS

- Smart-Lok[™] front differential
- FOX† 3.0 PODIUM RC2† shocks with bypass
- Belt monitoring system
- 850 W Magneto
- 7.6 in. (19.3 cm) digital display with keypad
- · X-package graphics/seats
- · 4-point harness with shoulder pads
- · Can-Am LED signature
- 14 in. (35.6 cm) cast-aluminum beadlock wheels
- · 32 in. (81.3 cm) Maxxis Carnivore† tires
- Full roof
- · HMWPE full skid plate

DIMENSIONS / CAPACITIES

DIIVIENSIONS / CAPACITIES	
Estimated Dry Weight **	1,924 lb (872.7 kg)
Chassis / Cage	Dual-phase 980 steel
LxWxH	165 x 72.7 x 68.5 in. (419.1 x 184.7 x 174 cm)
Wheelbase	135 in. (342.9 cm)
Ground Clearance	16 in. (40.6 cm)
Rack Capacity	150 lb (68 kg) with LinQ™ quick-attach
Storage Capacity	Total: 3 gal (11.4 L)
Fuel Capacity	10.5 gal (40 L)
	·
FEATURES	
Gauge	7.6 in. (19.3 cm) wide digital display with keypad

Gauge	7.6 in. (19.3 cm) wide digital display with keypad
Instrumentation	DC Outlet (10-A)
Magneto	850 W
Ingnition	RF Digitally Encoded Security System (D.E.S.S.™) with Start / Stop button
Lighting	LED headlights LED signature LED tail lights
Winch	N/A
Protection	Integrated front bumper Quarter-doors Full roof 4-point harness with shoulder pads HMWPE full skid plate Rear tow hook

WARRANTY

Factory warranty	2-year BRP limited warranty
•	

^{*149}kw/200hp based on MY22 U.S. EPA certification, or 145kw/195hp based on current EU NRMM certification





